



Hunan Kamuja Machinery & Equipment Co, Ltd









INTRODUCTION

Heavy duty forklift series FD, with many years of design and manufacturing experience, advanced technology. Products are widely used in logistics, stone processing, ports and terminals, and exported to foreign countries.

FEATURES

- ① The engine adopts a turbocharged engine with low fuel consumption, which has good power performance and large torque reserve.
- 2 The braking system adopts the mature products of the manufacture.

The brake is a disc brake, with fast heat dissipation, light weight, simple structure and convenient adjustment. It has good high temperature resistance performance under high load and stable braking effect.

- 3 The gearbox adopts domestic brand gearbox, which has good driving performance and traction performance. It is easy to maintain, economical and applicable, the accessories have good versatility.
- 4 The operating system adopts the pilot valve to control the working system. Simple, convenient and comfortable operation. While reducing the labor intensity of the driver, the work efficiency is improved.
- (5) Hydraulic system, double pump confluence, small system flow, low power consumption, stable performance.
- **(6)** The electrical system is equipped with maintenance-free batteries. Flame retardant wire and sheath, electrical components.
- 7The cab es luxurious with shock absorption, equipped with sunroof, heating and cooling air conditioner, wide field of vision and comfortable seat. With explosion-proof film, explosion-proof, heat insulation. Anti-glare, sound insulation.
- **®**The fork adopts high-strength, mature products of the manufacturer, which can double the service life.
- (9) Tire rim, no spoke steel rim, bear heavy load. Puncture-resistant high-strength tires.
- (10) Reinforced drive axle, high-strength heavy-duty planetary wheel-side reduction drive axle. The axle housing has higher strength and greater bearing capacity. With the stability and stability.





DETAILS





Cab & AC

Cummins Motor

LED Lights




Vehicle Lights


Alarm & Lights

Joystick


Digital Monitor







CAPACITY CHART



HUNAN KAMUJA MACHINERY & EQUIPMENT CO.,LTD.

Room 818, 4th Floor, Chang Tong Logistic Center, No.18 Qingzhuhu Road, Changsha, Hunan, China







OPTIONAL ATTACHMENTS









Multi-functional soft bag clip













Trash clip

Push-puller

Side shifter

Carton holder

Optional Devices and Accessories

- Tilt cylinder jacket
- Dual drive wheel
- Overhead exhaust device
- User specified color
- Cab heater
- Rear working light
- Alarm lamp
- Solid tyre

- Middle exhaust device
- Exhaust fire protection
- Suspension seat
- Weighing system
- Auxiliary hydraulic valve assembly
- Extinguisher
- Copper water tank
- LED rear light
- Double air filter

Optional Fittings

- Roll clip
- Rotate the flat clamp
- Load stabilizer
- Multi-purpose bucket clamp
- Soft clip
- Can clip
- Miter clamp
- Boom
- String rod

- Side yoke
- Swivel fork
- Fork extension cover
- Load ejector
- Carton clip
- Position ejector
- Bucket
- Lifting hook
- Extended fork

Special Equipment for Mast

- Wide view full free Stage II Mast
- Wide field of view full free Stage III Mast
- Special fork

HUNAN KAMUJA MACHINERY & EQUIPMENT CO.,LTD.






SPECIFICATIONS

Item	Specification		Unit	FD420
General	Rated Load		kg	42000
	Load center		mm	1250
Dimensions	Lift Height		mm	4000
	Fork Size(LxWxT)		mm	2600*300*130
	Fork Spread(outside)(Min/Max)			910/2830
	Mast Tilt Angle(F/R)		mm deg	6"/12"
	Fork Overhang		mm	1180
	Lenght without forks		mm	8170
	Overall width		mm	3600
	Mast Lowered Height		mm	5040
	Overhead Guard Height		mm	3820
	Outer Tuming Radius		mm	7730
Performance	Speed(Unload/Load)	Travel	Km/h	30/26
		Lifting	Mm/s	300
	Max gradeability(Load)		%	20
	Max drawbar pull(Load)		KN	
	Setvice Weight			240
Wheels&Tires	Tire	Front	kg	53000 4*18.00-25-28PR
		Rear		
	Tread	Front	mm	2*16.00-25-28PR
		Rear		2495
	Wheelbase		mm	2880
	WHEEIDASE		mm	5500
	Ground Clearance(Under mast)		mm	400
Power & Transmission	Battery	Voltage Capacity(5HR)	VA/h	2*12/150
	Engine	Model		WP12G375E350
		Manufacture		WeiChai
		Rated Output	Kw	276
		Rated Torque	N.m	1550
		No Of Cyinder		6
		Broe*Stroke	mm	126*155
		Dispiacement	L	11.6
	Transmissions	Manufacture		ZL80
	Stage FWD/RVS			4/4
	Operating Pressute		Мра	21

X The technical information may vary by the update policy, the changes will be without prior notice.

HUNAN KAMUJA MACHINERY & EQUIPMENT CO.,LTD.



Hunan Kamuja Machinery & Equipment Co.,Ltd

Address: Qingzhu Hu Road N.18, Chang Tong Logistic Center Floor 4 Room 818, Jinxia Economic Development Zone, Changsha City, Hunan Province, P.R of China.

333 SE 2nd Avenue Suit 2000 Miami FL 33131. USA

Tel: +86 731 8867 7248 e-mail: info@kamuja.cn

Web site: www.kamuja.cn



